

## Marked-Up Version of Substitute Specification

### SPECIFICATION

#### METHOD AND APPARATUS FOR MEASURING OXYGEN CONTENT

5

#### BACKGROUND

The present invention relates to a method for measuring the oxygen content in a sealed target space, particularly for monitoring inertization levels in an inert gas device for fire prevention and/or fire extinguishing, and to a device for carrying  
10 out the method.

In closed rooms containing equipment that is sensitive to water, such as DP areas, electrical switching and distribution rooms, or storage areas containing high-value goods, what are known as inertization methods are increasingly being utilized to reduce the risk of fires and to extinguish them. The extinguishing effect  
15 produced by this technique is based on the principle of oxygen displacement. As is generally known, normal ambient air consists of 21% oxygen, 78% nitrogen, and 1% other gasses by volume. In order to extinguish and prevent fires, the inert gas concentration in the relevant space is elevated, and so the proportion of oxygen is reduced, by infusing an inert gas such as pure nitrogen ~~which~~that displaces oxygen.  
20 Many substances no longer burn when the oxygen level drops below 15-18% by volume. It may be necessary to lower the oxygen level further to 12%, for example, depending on the combustible materials in the relevant room.

~~The patent DE 198 11 851 C2 describes~~Some known systems employ an inertization method with which a fire can be effectively extinguished given an  
25 optimally small storage capacity for the flasks of inert gas. According to this method, the oxygen content in the closed room is lowered to a base inertization level, ~~for instance (e.g., 16%),~~for instance (e.g., 16%), and in the event of fire, a very rapid full inertization ~~occurs (e.g., for instance an inertization to of 12% or lower, occurs).~~occurs (e.g., for instance an inertization to of 12% or lower, occurs).

An inert gas device for fire prevention and/or fire extinguishing for carrying  
30 out the cited inertization method ~~comprises~~includes the following components: an oxygen meter for measuring the oxygen content in the monitored target space; a fire

oxygen meter for measuring the oxygen content in the monitored target space; a fire detector for detecting a combustion parameter in the air of the target space; a control for evaluating the data of the oxygen meter and the combustion parameter detector and controlling the running of the inertization process; and an apparatus  
5 for producing inert gas and abruptly infusing it into the target space.

The term *combustion parameter* refers to physical quantities that underlie measurable changes in the environment of an incipient fire (e.g., for instance the ambient temperature, the proportion of solids, liquids, or gas in the ambient air (formation of smoke in the form of particulates, aerosols, or vapor) or the ambient  
10 radiation).

The oxygen meter serves for setting the base inertization level in the target space. If a threshold oxygen concentration value is exceeded, ~~for instance~~ such as due to a leak in the target space, the control sends a command to a separate system to infuse inert gas into the space, so that the oxygen proportion is reduced. The  
15 oxygen meter signals when the threshold value of the base inertization level has been reached again. The position of the base inertization level therein depends on properties of the room. But if the detector for combustion parameters senses a combustion parameter, however, the system receives a command to flood the room with inert gas until the oxygen concentration in the target space is reduced to a  
20 specified full inertization level.

The measuring of the oxygen content in the target space is ~~critical~~ important for a reliable ~~controlling~~ control of the method in this type of inert gas device for fire prevention and/or fire extinguishing. According to the prior art, the oxygen concentration in the target space is measured by point shaped oxygen  
25 sensors, which transmit the measurement values of the oxygen content to the control in the form of an analog signal. It is common to utilize 4-20 mA current interfaces, where 4 mA corresponds to a concentration of 0% oxygen, and 20 mA corresponds to the end of the measurement range (e.g., 25% oxygen). The disadvantage of utilizing point shaped oxygen sensors is that a greater number of  
30 such sensors are needed in the target space in order to get a representative reading of the oxygen content in the air in the room. That requires a correspondingly costly

cable ~~connection~~connections between the individual sensors that are distributed in the target space and the actual control. Furthermore, the control requires a correspondingly high number of analogous interfaces. This requires a particularly large and particularly expensive hardware outlay.

5        ~~But an~~An exceptionally disadvantageous aspect turns out to be that the control must continuously process a large number of signals. In particular, a forming of average values, ~~an estimation of~~estimating errors, and the ~~comparison~~comparing to preset threshold values require routines, which are absolutely indispensable for controlling the inertization process. Only with the aid  
10 of the processed data of the oxygen sensors is it possible to drive the system for infusing inert gas, a fresh air supply, or a fan for air circulation in the target space. The signal processing in the control is therefore very intensive and requires a high complexity of software.

#### SUMMARY

15        ~~Proceeding from the problem described above, the object of the~~The present invention is to ~~propose~~propose a method for measuring the oxygen content in a target space with which it is possible to determine the oxygen concentration effectively, reliably, and in representative fashion, and with an optimally small outlay for instrumentation and signal processing. This ~~object is~~ achieved by a  
20 method for measuring oxygen content ~~as described above comprising the following steps: First, including taking~~ an air sample ~~is taken~~ from the target space by means of a series of suction holes of a suction pipe system, so that the oxygen concentration of the air sample can then be determined by means of an oxygen detector.

25        ~~The inventive solution has~~present invention provides a number of substantial ~~advantages over the above described method~~benefits for measuring the oxygen content in a target space ~~which is known from the inert gas extinguishing technique~~. Air samples from various suction holes are mixed by suction ~~by way of~~through holes ~~of in~~ the suction pipe system. ~~The~~Thus, the oxygen concentration  
30 of the air sample ~~thus~~ automatically corresponds to an average value of the oxygen concentration of the target space, and the costly average value formation is omitted

from the signal processing in a control. In a simpler embodiment, software for evaluating the measurement values can even be omitted. Furthermore, ~~in the inventive method,~~ the monitored volume, (i.e., the measured volume), is substantially larger than in the case of oxygen sensors that are configured in points as in the prior art. This brings particular cost advantages in the purchasing, installation, and maintenance of the device for measuring the oxygen content in the target space and ultimately of the overall inert gas device for fire prevention and/or fire extinguishing.

~~The above cited object is further achieved by~~ present invention also includes a device for carrying out ~~this~~ the above method ~~which comprises~~ that includes at least one suction pipe system for drawing an air sample from the monitored target space through various holes. The ~~inventive~~ device realizes the ~~combining~~ combination of the inventive method with an oxygen meter in an ideal fashion. ~~Advantage is~~ Benefits are gained particularly by the ability to forgo the utilization of a plurality of point shaped oxygen sensors in the target space. Instead, at least one suction pipe system is provided for drawing an air sample from the monitored target space through various suction holes. That way, complicated cable connections between the former point shaped oxygen sensors and the control can also be omitted. An analog interface must still be provided in the control for the oxygen meter, but this can be realized with a small hardware outlay. Furthermore, the signal processing in the control is substantially simpler, since it is no longer necessary to process a large number of signals ~~off~~ from individual oxygen sensors. As a result, the software for signal processing can also be constructed correspondingly simple. It is ~~thus~~ therefore possible, ~~by means of the invention,~~ to measure the oxygen content at little expense in terms of instrumentation and signal processing, which brings economic benefits particularly in the purchase and maintenance of the inert gas system as a whole.

~~Advantageous developments of the method are cited in the subclaims 2 to 9, and advantageous developments of the device are cited in the claims 11 to 15.~~

Following the ~~second step,~~ the determination of the oxygen concentration of the drawn air sample by the oxygen sensor, the oxygen measuring method

comprises the following two steps: According to this development, includes comparing the measurement value of the oxygen concentration of the air sample is first compared to fixed threshold values in the oxygen sensor, and, in the case where the fixed threshold value is exceeded, reducing the oxygen concentration is reduced by an infusion of by infusing inert gas into the target space. The Thus, the inertization method is thus adapted to for possible leaks in the target space by means of the continuous measuring of the oxygen content. The specific advantage A benefit of this development is the existence of a separate “intelligence,” so to speak, in the inventive oxygen measuring method, in the sense that the method performs a comparison with predetermined threshold values of its own accord. A signal is sent to the control in the central unit only when a threshold value is crossed. This substantially reduces, not only the data traffic between the device for carrying out the inventive oxygen measuring method and the control of the inert gas device for fire prevention and/or fire extinguishing, but also substantially reduces the signal processing in the control. With this “distributed intelligence,” signal processing can be divided between the control and the oxygen sensor that is connected to it. This makes possible a substantial reduction in the software outlay, and particularly the purchase price and the maintenance outlay of the control of an inert gas device for fire prevention and/or fire extinguishing.

20           A detector for fire parameters is expediently integrated may be utilized in the inventive disclosed method for measuring the oxygen content in the target space. This detector sends a signal for full inertization in the event of fire. This development represents the procedural implementation of the combining of a known aspirative fire detector with the inert gas extinguishing technique. An aspirative fire detector is a fire detector that actively draws a representative subvolume of air from the room at a number of locations via a suction pipe system, conduit system, or duct system and then conducts these subvolumes to a detector for detecting a fire parameter. With the integrating integration of the detector of fire parameters into the device for carrying out the inventive disclosed method, an aspirative fire detector is created in addition to the oxygen measuring device. It is advantageous beneficial that existing components can be accessed for realizing this

aspirative fire detector. The target space can thus be equipped with an aspirative fire detector, thereby improving the fire detection, without additional outlay.

~~In a particularly advantageous embodiment~~another example of the ~~inventive solution, it is provided that~~disclosed method, the fire parameters sensed by the detector are smoke in the form of particulates, aerosols, or vapor, and at least one combustion gas. That way, the fire detector that is equipped with the ~~inventive~~disclosed oxygen meter reacts with particular sensitivity to the parameters that are typical of a fire. A fire can thus be detected in its incipient stage ~~already~~, and the inert gas device for fire prevention and/or fire extinguishing can be alarmed.

One ~~possible realization~~example of the inventive oxygen meter provides that the combustion gas that is sensed in the detector is CO or CO<sub>2</sub>. The advantage of this embodiment in particular is that the fire detector is especially sensitive to fire parameters and is also able to distinguish between an actual fire and cigarette smoke or other smoke-like quantities that are not characteristic of fire. Alternative embodiments are of course also imaginable.

In an ~~advantageous embodiment~~another example, the measurement of the air quality by a CO or CO<sub>2</sub> sensor is integrated into the method, and the fresh air supply of the target space is controlled in dependence on the signal of the CO or CO<sub>2</sub> sensor. The advantages that are discussed above in connection with the oxygen sensor are also brought to bear here. In particular, this advantageous embodiment forgoes the utilization of a plurality of CO or CO<sub>2</sub> sensors that are distributed in the target space and that measure pointwise, as well as the correspondingly large hardware and software outlay in the control for processing the signals.

~~A particularly advantageous inventive embodiment integrates a step in which~~Yet another example determines the oxygen concentration ~~is determined~~ by means of a reference oxygen sensor. This is done independently from the measuring of the above cited oxygen sensor. The reference oxygen sensor is permanently disposed in the air stream of the air sample that is drawn. For example, the reference oxygen sensor could be located in the immediate vicinity of

the oxygen sensor. The measurement value of the oxygen concentration that is acquired by means of the reference oxygen sensor is then compared to the measurement value of the oxygen concentration that was registered at the same time by the oxygen sensor in the air stream. It is provided that a disturbance signal is emitted if the comparison of the two measurement signals indicates that the deviation of the oxygen concentration value that was acquired by the oxygen sensor deviates from the oxygen concentration value acquired by the reference oxygen sensor deviates more than a previously defined tolerance value.~~[sic]~~ The comparison of measurement values and the output of the disturbance signal can occur in and by means of the oxygen sensor or the reference oxygen sensor. Alternative solutions are of course also imaginable.

~~In a particularly advantageous development of the above cited inventive embodiment~~another example, it is further provided that the reference oxygen sensor, as opposed to the oxygen sensor, is normally off. The reference oxygen sensor is switched on at regular intervals, ~~for instance~~such as once a day or once a week. Following activation, a minimum heating time is allowed to pass before the oxygen concentration in the air stream is determined. The activation process could occur with the aid of a signal that is generated by a clock timer. On the other hand, it would also be imaginable for the activation to occur at the push of a button, for instance in maintenance operations. Premature aging of the reference oxygen sensor can be prevented particularly easily by its being on only temporarily.

It is particularly ~~advantageous~~beneficial when the disturbance signal, which is ~~outputted~~output when the comparison of the two measurement values indicates that the oxygen concentration value acquired by the oxygen sensor deviates from the oxygen concentration value acquired by the reference oxygen sensor by more than a previously defined tolerance value, is utilized to the effect that the reference oxygen sensor remains on permanently and, therefore, continuously delivers measurement values of the oxygen concentration of the drawn air sample. These measurement values are then evaluated instead of those of the oxygen sensor. Measurement uncertainties that are caused by the aging of the oxygen sensor when it is continuously driven can thus be eliminated.

According to an ~~advantageous development~~example of the ~~inventive~~a device, inertization levels in the target space are set by a control, which also controls the fresh air supply and a fan, whereby at least one oxygen sensor is provided for measuring the oxygen concentration in an air sample that is drawn  
5 from the target space, and at least one detector is provided for detecting fire parameters in an air sample drawn from the target space by one of the suction pipe systems. ~~This represents an embodiment of the inventive~~Such a device that is particularly easy to realize, in which the measuring components that are utilized in the inert gas device for fire prevention and/or fire extinguishing are ~~advantageously~~  
10 utilized only for analyzing the air sample drawn from the target space.

At least one CO or CO<sub>2</sub> sensor for measuring the air quality in an air sample drawn from the target space by one of the suction pipe systems is expediently provided. ~~The inventive solution can thus be developed so that~~Thus, the air quality can also be monitored by the inventive inert gas device for fire prevention and/or  
15 fire extinguishing.

An oxygen sensor and a detector for detecting fire parameters and/or a CO or CO<sub>2</sub> sensor are ~~advantageously~~ integrated in a suction pipe system. The number of components that are utilized in the inert gas device for fire prevention and/or fire extinguishing can thus be reduced. This brings additional economic benefits in the  
20 purchase, installation and maintenance of an inert gas device for fire prevention and/or fire extinguishing.

In ~~one possible realization~~an example, electrochemical cells consisting of zirconium dioxide are utilized as oxygen sensors. Zirconium dioxide based oxygen sensors are known from automotive technology, where they are used in catalytic  
25 converters to measure the oxygen content in exhaust gasses. The sensors are considered reliable, sensitive, sturdy and low-maintenance components. The ~~invention~~disclosed device can be realized particularly cost-effectively if standard components are utilized in the inventive device.

In a further ~~development of the inventive device~~example, it is provided that,  
30 besides the oxygen sensor, a reference oxygen sensor is utilized for measuring the oxygen concentration of the air sample that is drawn from the target space. This



serves as a reference relative to the oxygen sensor and lies continuously in the air stream, though the sensor is normally off. This prevents the aging of the reference oxygen sensor. The sensor is activated at regular intervals (e.g., once a day or once a week). The signal for activating the reference sensor is generated by a clock timer, for example. It can also be generated at the push of a button, for instance for maintenance operations. Following the activation of the reference oxygen sensor, the minimum heating time is allowed to pass. Then the two measurement values of the oxygen sensor and the reference sensor are compared. If the difference between the two values is larger than a predetermined threshold, a disturbance is signaled, and the reference oxygen sensor is no longer switched off. Its measurement values are evaluated instead of those of the aged oxygen sensor.

~~A preferred exemplifying embodiment of the inventive device for measuring the oxygen content in a closed target room for the purpose of monitoring inertization levels in an inert gas device for fire prevention and/or fire extinguishing will now be laid out in detail with the aid of drawings. Shown are:~~

#### BRIEF DESCRIPTION OF THE FIGURES

~~FigFIG. 1; illustrates a schematic block diagram of an exemplifying embodiment of the inventive device for measuring the oxygen content in an inert gas device for fire prevention and/or fire extinguishing;~~

~~FigFIG. 2; illustrates a schematic representation of the inventive device for measuring the oxygen content in a closed target space.~~

#### DETAILED DESCRIPTION OF THE PRESENT EXAMPLES

~~FigFIG. 1 represents a schematic block diagram of an exemplifying embodiment of the inventive device for measuring the oxygen content in an inert gas device for fire prevention and/or fire extinguishing 6. The inert gas device for fire prevention and/or fire extinguishing 6 serves for preventingto prevent and extinguishingextinguish fires in the closed target space 10. Two suction pipe systems 1 for sucking air samples through various holes 2 are provided in the target space 10. The suction pipe systems 1 are each equipped with a suction sensor 8 in which the air samples from the target space 10 are conducted to an oxygen sensor 3~~

and to a detector 4 for detecting fire parameters, namely a CO or CO<sub>2</sub> sensor 5. In the embodiment represented in Fig. 1, two suction pipe systems 1 are represented, one of which is mounted below the ceiling of the target space 10 at a distance of up to 1 m therefrom as warranted, and the other of which is advantageously mounted at breathing height, i.e., approximately 1.5 m above the floor.

The oxygen sensor 3a determines the oxygen concentration of the respective air sample and compares the measurement value to fixed threshold values. If the fixed threshold value is exceeded, the oxygen sensor 3a sends a signal to a control 7 over a data line, which effectuates an infusion of inert gas into the target space 10 and a reduction of the oxygen concentration. For that purpose, the control 7 signals an apparatus for producing and infusing inert gas 6 to perform an inertization of the target space 10.

Based on the continuous drawing of air samples from the target space 10 by the aspirative suction device, the oxygen content of the air in the room is continuously measured in the oxygen sensor 3a. As soon as the oxygen concentration of the continuously drawn air sample in the oxygen sensor 3a matches a fixed threshold value, the control 7 receives a corresponding signal to discontinue inertization.

In the embodiment example represented in Fig. 1, in addition to smoke in the form of particulates, aerosols, or vapor, at least one combustion gas such as CO or CO<sub>2</sub> is also sensed in the detector 4 for detecting fire parameters. By utilizing at least two different fire parameters that can independently establish the presence of a fire in the target space 10, it is possible to realize an optimal redundancy and a corresponding fail-safety of the inert gas device for fire prevention and/or fire extinguishing 6. In particular, the detector 4 is also able to distinguish between an actual fire and cigarette smoke or similar smoke-like quantities that are not characteristic of fire.

In another suction pipe system 1 according to Fig. 1, a CO or CO<sub>2</sub> sensor 5 and a detector 4 for detecting fire parameters are integrated in the suction sensor. The CO or CO<sub>2</sub> sensor 5 monitors the air quality of the target space 10 by

determining the CO or CO<sub>2</sub> content of the air sample that is drawn by the suction pipe system. If the air quality of the target space 10 no longer corresponds to the expected standards, the sensor 5 ~~signals~~signals this to the central control 7, which drives a fan 9 for air circulation, or respectively, fresh air supply 11. If a  
5 sufficiently improved air quality is subsequently measured, the fan 9 or fresh air supply 11 then switches off again.

It is also possible to integrate several different sensors in a suction sensor 8, for instance a CO or CO<sub>2</sub> sensor 5 in combination with a detector 4 for detecting fire parameters but also an oxygen sensor 3a in combination with one of the other  
10 sensors 4 or 5 cited above.

~~In an embodiment of the inventive device, besides~~Besides the oxygen sensor 3a, a reference oxygen sensor 3b ~~is~~may be also utilized for measuring the oxygen concentration of the air sample drawn from the target space 10. This serves as a reference relative to the oxygen sensor 3a and lies in the air stream at all times  
15 but is normally switched off. This prevents the aging of the reference oxygen sensor 3b. The sensor 3b is switched on at regular intervals (e.g., once a day or once a week). The signal for switching on the reference oxygen sensor 3b is generated by a clock timer. It can also be generated at the push of a button, for instance in maintenance operations. Following the activating of the reference  
20 oxygen sensor 3b, a minimum heating time is allowed to pass. The two measurement values of the oxygen sensor 3a and the reference sensor 3b are then compared. If the difference between the two measurement values is greater than a defined threshold, a disturbance is signaled, and the reference oxygen sensor 3b is no longer switched off. Its measurement values are evaluated instead of those of  
25 the aged oxygen sensor 3a.

~~Fig~~FIG. 2 is a schematic representation of ~~the inventive~~another exemplary device for measuring the oxygen content in a closed room 10. In this ~~embodiment~~example, the suction pipe system 1 is attached beneath the ceiling of the target room 10 by means of pipe straps 12. Air is drawn from the target space  
30 10 through the holes 2 in the suction pipe system 1. To that end, a suction unit 13 that is integrated in the suction sensor 8 is utilized. The suction unit 13 and the

suction pipe system 1 are monitored by means of an air stream sensor 14 which is disposed at the end of the suction pipe system 1.

After passing the air stream sensor 14, the air sample passes the oxygen sensor 3a. The oxygen sensor 3a measures the oxygen concentration of the air sample, which represents an average value of the oxygen concentration of the air of the target space 10. The average value is compared to threshold values in the oxygen sensor 3a. If the threshold values are exceeded, the oxygen content in the air of the target space 10 is too high to prevent a fire reliably. At the appearance of the signal *over a first threshold value*, the control 7 drives the device that generates the inert gas and infuses ~~it~~the inert gas into the target space 10 (i.e., a generator).

If the oxygen content continues to rise, this indicates a defective generator ~~which~~that cannot infuse inert gas into the space 10. At the appearance of the signal *over a second threshold value*, the control 7 signals *disturbance*.


If the values are below the threshold values, a full inertization is not triggered. At the appearance of the signal *under a first threshold value*, the control 7 stops the generator ~~7~~ because the desired oxygen content has been achieved.

If the oxygen content continues to drop, this indicates a defective generator ~~which~~that is no longer stopping the infusion of inert gas into the target space 10. At the appearance of the signal *below a second threshold value*, the control 7 signals *disturbance*.

If the oxygen content falls below a value that is dangerous to humans, personal safety measures are initiated. At the signal *below a third threshold value*, the control 7 triggers personal safety measures such as the evacuation of the room or the blocking of entry.

Instead of the oxygen sensor 3a, a CO or CO<sub>2</sub> sensor 5 and/or a detector 4 for detecting fire parameters can be utilized in the suction sensor 8.

~~The invention is not limited to the exemplifying embodiments described in connection with Figures 1 and 2; rather, a number of variants are also possible.~~



Reference Characters

5 Although preferred examples of the methods and apparatus have been disclosed for illustrative purposes, those of ordinary skill in the art will appreciate that the scope of this patent is not limited thereto. On the contrary, this patent covers all methods and apparatus found within the scope of the appended claims.

### ABSTRACT OF THE DISCLOSURE

~~The invention relates to a~~ A method and apparatus for measuring the oxygen content in a closed target space ~~(10)~~, particularly for monitoring inertization levels in an inert gas device for fire prevention and/or fire extinguishing ~~(15)~~, ~~and a device for carrying out the method.~~ Toward the aim of proposing a method for measuring the oxygen content in a target space ~~(10)~~ with which an effective, certain, and representative determination of the oxygen concentration can be achieved for an optimally small expenditure in instrumentation and signal processing, the method provides that air samples are drawn from the target space ~~(10)~~, and the oxygen concentration of the air samples is determined. ~~The device~~ An apparatus is equipped with a suction pipe system ~~(1)~~ for sucking the air sample from the target space ~~(10)~~ through various holes ~~(2)~~ so that it can carry out the method.